

ECO VAPOR

High pressure steam generator 3.5bar. Available in 3 models. All functions are electronically controlled through an electronic plate. With 25lit water tank, service tank for the boiler blow-off and wheels for easy transport. The ECO series steam generators **comply with all the safety regulations, have been tested by the TUV institute and bear TRD801 safety certificates and CE conformity certificate to all regulations and guidelines set out by the European Union.**

Steel boiler : 8.5 lit
Operating pressure : 3.5 bar
Test pressure : 6 bar


ECO SERIES STEAM GENERATOR MODEL RANGE

MODEL	FEATURES	STEAM PRODUCTION	HEATING
ECO VAPOR/ 1-2,5 CODE 103-06-004	With 1 steam valve. Steam supply for 1 iron	3.25 kg/hour	2.5KW 230V-1ph-50Hz
ECO VAPOR/ 1-4 CODE 103-06-003	With 1 steam valve. Steam supply for 1 iron	5.2 kg/hour	4KW 230V-1ph-50Hz
ECO VAPOR/ 2-4 CODE 103-06-001	With 2 steam valves. Steam supply for 2 irons	5.2 kg/hour	4KW 230V-1ph-50Hz
ECO VAPOR/ 2-4 CODE	With 2 steam valves. Steam supply for 2 irons	5.2 kg/hour	4KW 400V-3ph-50Hz